


HIGH FREQUENCY, WITH BUILT-IN CAPACITORS SMD WASHABLE CERAMIC RESONATORS AWSCR



7434, 4741, 3731, 2520

FEATURES:

- Low resonant impedance.
- Excellent environmental resistance.
- Reflow capable.
- High stability washable type.
- Industrial grade.
- Built-in load capacitance.

APPLICATIONS:

- Remote controls.
- Electric appliances.
- Mobile phones, DVD, CD-Rom.
- Microprocessor clocks.
- Automotive controllers.
- Industrial controllers.

STANDARD SPECIFICATIONS

Abracon P/N	Freq. range (MHz)	Resonant Impedance Ω max.	Frequency tolerance	Frequency stability @-20°C to +80°C	Aging in 10 years	Operating temperature	Package Style *
AWSCR[] MGS MGD MGA	2.0~7.99	100 Ω for $2.0 < F < 3.0$ MHz 50 Ω for $3.0 \leq F < 3.5$ MHz 30 Ω for $3.5 \leq F \leq 7.99$ MHz	$\pm 0.5\%$	$\pm 0.3\%$	$\pm 0.3\%$	-20°C to +80°C -40°C to +85°C -40°C to +125°C	7434
AWSCR[] MTS MTD MTA	8.0~13.0	25 Ω	$\pm 0.5\%$	$\pm 0.3\%$	$\pm 0.3\%$	-20°C to +80°C -40°C to +85°C -40°C to +125°C	4741
AWSCR[] MVS MVD MVA	8.0~13.0	25 Ω	$\pm 0.5\%$	$\pm 0.3\%$	$\pm 0.3\%$	-20°C to +80°C -40°C to +85°C -40°C to +125°C	3731
AWSCR[] MXS MXD MXA	13.01~50.0	40 Ω	$\pm 0.5\%$	$\pm 0.3\%$	$\pm 0.3\%$	-20°C to +80°C -40°C to +85°C -40°C to +125°C	4741
AWSCR[] MCS MCD MCA	13.01~50.0	40 Ω	$\pm 0.5\%$	$\pm 0.3\%$	$\pm 0.3\%$	-20°C to +80°C -40°C to +85°C -40°C to +125°C	3731
AWSCR[] MSS MSD MSA	20.0~50.0	40 Ω For ≤ 32 MHz 50 Ω For ≤ 40 MHz 60 Ω For ≤ 50 MHz	$\pm 0.5\%$	$\pm 0.3\%$	$\pm 0.3\%$	-20°C to +80°C -40°C to +85°C -40°C to +125°C	2520

*Please see package options and dimensions on page 35A

Please check for availability on M[]D and M[]A Series

Frequency stability: M[]D: $\pm 0.5\%$ typ. -40°C to +85°C
M[]A: $\pm 0.7\%$ typ. -40°C to +125°C

Storage temperature: -40°C to +125°C

We perform IC characterization to match your application.

Please call us for details.


Packaging: Option Tape and Reel (1,000 pcs.) see appendix H.

Marking, see appendix G. Application notes, see appendix A.

Environmental and mechanical specification, see appendix C. Group 6.

Recommended handling, see appendix F.

Test Circuit



- U1: CD4069UB
74HCU04
Y1: RESONATOR
C1 C2 (Built-in)
- 30pF $\pm 20\%$ (MG and MT Series)
15pF $\pm 20\%$ (MV Series)
15pF $\pm 20\%$ for $F < 26$ M (MX series)
10pF $\pm 20\%$ for $26\text{M} \leq F \leq 50\text{M}$ (MX series)
10pF $\pm 20\%$ (MC Series)
8pF $\pm 20\%$ (MS Series)

ORDERING OPTIONS

AWSCRMXX - Packaging

G, T, V, X, C or S - T (Tape and reel)
S, D or A

NOTE: Left blank if standard • All specifications and markings subject to change without notice

ABRACON IS
ISO 9001 / QS 9000
CERTIFIED


29 Journey • Aliso Viejo, CA 92656 • USA
(949) 448-7070 • FAX: (949) 448-8484

E-MAIL: abinfo@abracon.com • INTERNET ADDRESS: www.abracon.com

ABRACON
CORPORATION


37
Rev. B
01/2003

HIGH FREQUENCY, WITH OR WITHOUT BUILT-IN CAPACITORS SURFACE MOUNT CERAMIC RESONATORS ASZT, ASCR, AWSZT, AWSCR




ASZT or AWSZT

ASCR or AWSCR




7434

Recommended Land Pattern




Dimensions: mm




7434

Recommended Land Pattern




Dimensions: mm

Pin	Function
1	Input
2	GND
3	Output




4741

Recommended Land Pattern




Dimensions: mm




7441

Recommended Land Pattern




Dimensions: mm




3731

Recommended Land Pattern




Dimensions: mm




3731

Recommended Land Pattern




Dimensions: mm




2520

Recommended Land Pattern




Dimensions: mm



2520

Recommended land pattern



Dimensions: mm

ABRACON IS
ISO 9001 / QS 9000
CERTIFIED

NOTE: Left blank if standard • All specifications and markings subject to change without notice

29 Journey • Aliso Viejo, CA 92656 • USA
(949) 448-7070 • FAX: (949) 448-8484

E-MAIL: abinfo@abracon.com • INTERNET ADDRESS: www.abracon.com

ABRACON®
CORPORATION 35A

Washability Specification

**This product can be washed using the following solvents
under the suggested conditions:**

Solvents:
HCFC, Isopropyl Alcohol, Trichloroethane, Tap water, Demineralized Water, Pine Alpha ST-100S
Ultrasonic Wash:
Less than 1 min. (Frequency:28KHz,Ouput:20W/L) Immersion Wash or others: Less than 5 min.
Solvents temperature should be at 60°C or under 60°C
Drying:
By air blow at 80°C max.